#### Revision no. 8 ALI Group S.r.l. Revision date 13/09/2018 Printed on 13/09/2018 **COMBICLEAN** Page no. 1/12

## **Safety Data Sheet**

Compliant with Annex II of REACH - Regulation 2015/830

## SECTION 1. Identification of the substance/mixture and company/firm

1.1. Product identifier

Code: ZARA F4 COMBICLEAN Name **OVEN DETERGENTS** Chemical name and synonyms

#### 1.2. Identified uses related to the substance or mixture and recommended uses

Description/Use **ALKALINE OVEN DETERGENT** 

Identified Uses Industrial Professional Consumption oven detergent

#### Uses advised against

Do not use for uses other than those indicated

#### 1.3. Information about the supplier of the safety data sheet

Company name ALI Group S.r.I. **VIA SCHIAPARELLI 15** Address City and country 31029 VITTORIO VENETO (TV) **ITALY** 

tel. +39 0438 9110

fax -

email address of the contact person,

In charge of the safety data sheet lainox@lainox.com Head of market release: ALI Group S.r.l.

#### 1.4. Emergency telephone number

For urgent information, please contact Poison Control Centre Bambino Gesù Children's Hospital, Piazza Sant'Onofrio, 4 00165

Rome Tel.: +39 0668593726

Univ. Hosp. of Foggia, V.le Luigi Pinto, 1 71122 Foggia Tel.: +39 0881732326 Hosp. of A. Cardarelli, Via A. Cardarelli, 9 80131 Naples Tel.: +39 0817472870

Umberto I Polyclinic Poison Control Centre, V.le del Policlinico, 155 00161 Rome Tel.: +39 0649978000

A. Gemelli Polyclinic Poison Control Centre, Largo Agostino Gemelli, 8 00168 Rome

Tel.: +39 063054343

Univ. Hosp. of Careggi Medical Toxicology, Largo Brambilla, 3 50134 Florence Tel.: +39

0557947819

National Poison Control Centre for Toxicology Information, Via Salvatore Maugeri, 10 27100 Pavia Tel.: +39 038224444

Hosp. of Niguarda Ca' Granda, Piazza Ospedale Maggiore,3 20162 Milan Tel.: +39

Papa Giovanni XXII Hospital, Piazza OMS, 1 24127 Bergamo Tel.: +39 800883300

#### **SECTION 2. Hazard identification**

## 2.1. Classification of the substance or mixture

Revision no. 8

Revision date 13/09/2018

Printed on 13/09/2018

Page no. 2/12

**COMBICLEAN** 

The product is classified as hazardous pursuant to the provisions under Regulation (EC) 1272/2008 (CLP) (and successive amendments and repeals). The product, therefore, requires a safety data sheet that complies with the provisions of Regulation (EU) 2015/830.

Any additional information regarding the risks for health and/or the environment are outlined in sections 11 and 12 of this data sheet.

Hazard classification and indications:

H314 Skin corrosion, category 1A Causes severe skin burns and eye damage.

Severe eye damage, category 1 H318 Causes serious eye damage.

#### 2.2. Label elements

Hazard labelling pursuant to Regulation (EC) 1272/2008 (CLP) and successive amendments and repeals.

Hazard pictograms:



Cautions: Hazard

Hazard indications:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

P303+P361+P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

SODIUM HYDROXIDE Contains:

#### 2.3. Other hazards

Based on the available data, the product does not contain PBT or vPvB substances in percentages over 0.1%.

## **SECTION 3. Composition/information about the ingredients**

#### 3.1 Substances

Information not applicable

3.2. Mixtures

Contains:

Identification Classification 1272/2008 (CLP) x = Conc. %

**SODIUM HYDROXIDE** 

## **COMBICLEAN**

Revision no. 8

Revision date 13/09/2018

Printed on 13/09/2018

Page no. 3/12

CAS 1310-73-2

 $12 \le x < 13.5$ 

Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318

EC 215-185-5

INDEX 011-002-00-6

Reg. No. 01-2119457892-27

**SODIUM HYDROXIDE** 

CAS 1310-73-2

 $2.5 \le x < 3$ 

Skin Corr. 1A H314, Eye Dam. 1 H318

EC 215-185-5

INDEX 011-002-00-6

Reg. No. 01-2119457892-27

CARBOXYLIC ACID OF ALLYL

**ALCOHOL** 

polymer  $1 \le x < 2$ 

Skin Irrit. 2 H315; , Eye Dam. 1 H318

The complete test of the hazard indications (H) is outlined in section 16 of the data sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove any contact lenses. Rinse immediately with plenty of water for at least 30/60 minutes, while holding the eyelids apart. Seek medical advice immediately.

SKIN: Remove any contaminated clothing. Take a shower immediately. Seek medical advice immediately.

INGESTION: Drink as much water as possible. Seek medical advice immediately. Do not induce vomiting unless expressly authorised by medical personnel.

INHALATION: Seek medical advice immediately. Take the patient outside, away from the site of the accident. If the patient stops breathing, administer artificial respiration. Adopt suitable precautions for the responder.

### 4.2. Main symptoms and effects both acute and delayed

No specific information is known about the symptoms and effects caused by the product.

#### 4.3. Indication of any requirement to immediately seek medical advice and special treatments

Information not available

## **SECTION 5. Fire prevention measures**

## 5.1. Extinguishing agents

SUITABLE EXTINGUISHING AGENTS

The extinguishing agents are the conventional kind: carbon dioxide, foam, powder and nebulised water.

UNSUITABLE EXTINGUISHING AGENTS

None in particular.

#### 5.2. Special hazards caused by the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE Avoid breathing in combustion products.

#### 5.3. Recommendations for fire fighters

GENERAL INFORMATION

ALI Group S.r.I.	Revision no. 8
• • • • • • • • • • • • • • • • • • •	Revision date 13/09/2018
COMBICLEAN	Printed on 13/09/2018
	Page no. 4/12

Cool the containers with water jets to prevent the decomposition of the product and the development of substances which could be a health hazard. Always wear the full fire prevention protection equipment. Collect the water used to put out the fire which must not be discharged into the drains. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

EQUIPMENT

Normal firefighting clothing, such as an open circuit, compressed air self-contained breathing apparatus (EN 137), firefighting suit (EN469), protective gloves (EN 659) and firefighter boots (HO A29 or A30).

#### **SECTION 6. Measures in the event of accidental spills**

#### 6.1. Personal precautions, protection equipment and procedures in the event of an emergency

Stop the leak if there is no hazard.

Wear suitable protective equipment (including the personal protective equipment under section 8 of the safety data sheet) in order to prevent contamination of the skin, eyes and personal clothing. These indications are valid both for processing technicians and for emergency interventions.

#### 6.2. Environmental precautions

Prevent the product from entering the sewage systems, water courses and ground water.

#### 6.3. Methods and material for containment and cleaning up

Suction the leaked product into a suitable container. Assess the compatibility of the container to use with the product, by checking against section 10. Absorb the remaining product with inert absorbent material.

Ensure adequate ventilation. Disposal of the contaminated material must be carried in compliance with the provisions of point 13.

#### 6.4. Reference to other sections

Any information about individual protection and the disposal are outlined in sections 8 and 13.

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Handle the product after consulting all the other sections of this safety data sheet. Do not disperse of the product in the environment. Do not drink, eat or smoke when using. Remove contaminated clothing and protective equipment before entering eating areas.

#### 7.2. Conditions for safe storage, including any incompatibilities

Only store in the original container. Keep the containers closed in a well-ventilated place, away from direct sunlight. Keep the containers away from any incompatible material, checking against section 10.

#### 7.3. Specific end uses

Information not available

## ALI Group S.r.I. Revision no. 8 Revision date 13/09/2018 Printed on 13/09/2018 Page no. 5/12

## **SECTION 8. Exposure control/personal protection**

#### 8.1. Control parameters

Legislative references:

GBR United Kingdom

EH40/2005 Workplace exposure limits

GRC Ελλάδα ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012

SODIUM HYDROXIE Threshold limit value						
Туре	State	State TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
WEL	GBR			2		
TLV	GRC	2		2		
TLV-ACGIH				2 (C)		

Health - Derived No-Effect Level - DNEL / DMEL										
	Effects on				Effects on					
	consumers				workers					
Exposure pathway	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic		
				systemic		systemic		systemic		
Inhalation		•	1 mg/m3	-		-	1 mg/m3			

SODIUM HYDROXIDE Threshold limit value					
Туре	State	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
WEL	GBR			2	
TLV	GRC	2		2	
TLV-ACGIH				2 (C)	

Health - Derived No-Effect Level - DNEL / DMEL									
	Effects on				Effects on				
	consumers				workers				
Exposure pathway	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic	
				systemic		systemic		systemic	
							4 / 0		

 Inhalation
 1 mg/m3
 1 mg/m3

Key:

(C) = CEILING; INALAB = Inhalable fraction; RESPIR = Breathable fraction; TORAC = Thoracic fraction.

VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

## 8.2. Exposure control

Considering that the use of adequate technical measures should always take priority over personal protection equipment, ensure good ventilation in the workplace through effective local extraction.

When choosing personal protective equipment, ask your chemical substance suppliers for any advice.

Personal protective equipment must bear the CE marking which indicates compliance with the laws in force.

## ALI Group S.r.I. Revision no. 8 Revision date 13/09/2018 Printed on 13/09/2018 Page no. 6/12

Provide emergency shower facilities with eye baths.

#### HAND PROTECTION

Protect hands with category III work gloves (ref. standard EN 374).

When choosing the material of the work gloves, you should consider: compatibility, degradation, breakthrough times and permeation rates.

In the case of preparations, resistance of work gloves to chemical agents must be checked before use, as it is unpredictable. Gloves have a deterioration time that depends on the duration and method of use.

#### SKIN PROTECTION

Wear work clothes with long sleeves and safety footwear for professional use, category III (ref. Directive 89/686/EEC and EN ISO 20344 standard). Wash with soap and water after removing protective clothing.

#### EYE PROTECTION

Physical state

Colour

It is advisable to wear a hooded visor or protective visor combined with tightly fitting goggles (ref. standard EN 166).

## RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) of the substance or one or more substances present in the product are exceeded, it is advisable to wear a mask with a type B filter. The class (1, 2 or 3) must be chosen in relation to the limit of use of the concentration. (ref. standard EN 14387). If gases or vapours and/or gases of vapours with particles (aerosols, fumes, mist, etc.), combined filters must be provided.

The use of measures to protect the airways is required if the technical measures are not sufficient to limit the exposure of workers to the threshold values taken into account. The protection offered by the mask is, however, limited.

If the substance is considered odourless or its odour threshold is above the one for TLV-TWA and in the event of any emergency, wear an open circuit, compressed air self-contained breathing apparatus (ref. standard EN 137) or a fresh air hose breathing apparatus (ref. standard EN 138). For the correction choice of respiratory protection devices, refer to standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROL

Emissions from production processes, including those from ventilation equipment, should be checked for compliance with environmental protection regulations.

#### **SECTION 9. Physical and chemical properties**

#### 9.1. Information about fundamental physical and chemical properties

liquid

vellow

Odour odourless Odour threshold Not available Not available Melting or freezing point Initial boiling point Not available Boiling range Not available Flash point Not available Evaporation rate Not available Flammability of solids and gases not applicable Lower flammability limit Not available Upper flammability limit Not available Not available Lower explosive limit Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density Not available Solubility soluble partition coefficient: octanol/water Not available Auto-ignition temperature Not available Decomposition temperature Not available Viscosity Not available

Explosive properties not classified as explosive, does not contain explosive substances according

to Reg. CLP Art. (14 (2))

Oxidising properties the product is not an oxidising substance

# ALI Group S.r.I. Revision no. 8 Revision date 13/09/2018 Printed on 13/09/2018 Page no. 7/12

#### 9.2. Other information

Information not available

## **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are not particular reaction hazards with other substances under normal conditions of use.

#### 10.2. Chemical stability

The product is stable under normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseen under normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However, the usual precautions used for chemical products should be respected.

#### SODIUM HYDROXIDE

Avoid exposure to: air, humidity, heat sources.

## SODIUM HYDROXIDE

Avoid exposure to: air, humidity, heat sources.

#### 10.5. Incompatible materials

#### SODIUM HYDROXIDE

Incompatible with: strong acids, ammonia, zinc, lead, aluminium, water, flammable liquids.

#### SODIUM HYDROXIDE

Incompatible with: strong acids, ammonia, zinc, lead, aluminium, water, flammable liquids.

## 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

In the absence of experimental toxicological data on the product in question, the possible dangers of the product to the health have been assessed on the basis of the properties of the substances it contains, according to the criteria laid down by the reference legislation for classification.

Therefore, consider the concentration of the individual hazardous substances which may be mentioned in section. 3, when assessing the toxicological

## COMBICLEAN

Revision no. 8

Revision date 13/09/2018

Printed on 13/09/2018

Page no. 8/12

effects caused by exposure to the product.

#### 11.1. Information about the toxicological effects

Metabolism, kinetics, mechanism of action and other information

Information not available

Information on probable exposure pathways

Information not available

Immediate or delayed effects and chronic effects due to short or long-term exposure

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

LC50 (Inhalation) of the mixture:
Unclassified (no significant component)
LD50 (Oral) of the mixture:
Unclassified (no significant component)
LD50 (Skinn) of the mixture:
Unclassified (no significant component)

#### SKIN CORROSION/SKIN IRRITATION

Corrosive for the skin

#### SERIOUS EYE DAMAGE/EYE IRRITATION

Causes serious eye damage

#### RESPIRATORY OR SKIN SENSITISATION

Does not respond to classification criteria for this hazard class

## GERM CELL MUTAGENICITY

Does not respond to classification criteria for this hazard class

#### CARCINOGENICITY

Does not respond to classification criteria for this hazard class

### REPRODUCTIVE TOXICITY

Does not respond to classification criteria for this hazard class

#### SPECIFIC TARGET ORGAN TOXICITY (STOT) - SINGLE EXPOSURE

## **COMBICLEAN**

Revision no. 8

Revision date 13/09/2018

Printed on 13/09/2018

Page no. 9/12

Does not respond to classification criteria for this hazard class

#### SPECIFIC TARGET ORGAN TOXICITY (STOT) - REPEATED EXPOSURE

Does not respond to classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not respond to classification criteria for this hazard class

## **SECTION 12. Ecological information**

Use according to good working practice, avoiding dispersion of the product in the environment. Notify the competent authorities if the product reaches water courses or if it has contaminated the soil or vegetation.

#### 12.1. Toxicity

SODIUM HYDROXIDE

EC50 - Crustaceans 40.4 mg/l/48h Ceriodaphnia sp.

SODIUM HYDROXIDE

EC50 - Crustaceans 40.4 mg/l/48h Ceriodaphnia sp.

CARBOXYLIC ACID OF ALKYL ETHER

LC50 - Fish > 100 mg/l/96h

## 12.2. Persistence and degradability

SODIUM HYDROXIDE

Degradability: data not available

SODIUM HYDROXIDE

Degradability: data not available

#### 12.3. Bioaccumulation potential

Information not available

## 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

Based on the available data, the product does not contain PBT or vPvB substances in percentages over 0.1%.

#### 12.6. Other adverse effects

#### Revision no. 8 ALI Group S.r.l. Revision date 13/09/2018 Printed on 13/09/2018 **COMBICLEAN** Page no. 10/12

Information not available

## **SECTION 13. Advice for disposal**

#### 13.1. Waste treatment methods

Re-use, if possible. Product residue should be treated as special hazardous waste. The hazardous properties of waste that partly contain this product must be assessed according to the laws in force.

Disposal must be carried out by a company authorised for waste management, in compliance with the national and local legislation. CONTAMINATED PACKAGING

Contaminated packaging must be sent for recovery or disposal in compliance with national laws for waste management.

## **SECTION 14. Transport information**

14.1. UN NUMBER

ADR / RID, IMDG, IATA: 1824

14.2. UN-Shipping Name

CAUSTIC ALKALI LIQUID, SODIUM HYDROXIDE N.A.S. ADR / RID: IMDG: CAUSTIC ALKALI LIQUID, SODIUM HYDROXIDE N.O.S. IATA: CAUSTIC ALKALI LIQUID, SODIUM HYDROXIDE N.O.S.

14.3. Transport hazard classes

ADR / RID: Class: 8 Label: 8 IMDG: Class: 8 Label: 8 IATA: Class: 8 Label: 8

14.4. Packing group

ADR / RID, IMDG, IATA: ΙΙ

14.5. Environmental risks

NO ADR / RID: IMDG: NO NO IATA:

14.6. Special precautions for users

HIN Kemler 80 Limited Tunnel restriction ADR / RID:

Quantities: 1 L code: (E)

Special provision: -

EMS: F-A, S-B IMDG: Limited

Quantities: 1 L

IATA Maximum Cargo **Packing** 

> Quantities: 30 L instructions: 855 Pass. Maximum Pack ing Quantities: 1 L instructions: 851

Special instructions:

A3, A803

14.7. Dry bulk carrier according to annex II of MARPOL and IBC code N.A.

## COMBICLEAN

Revision no. 8

Page no. 11/12

Revision date 13/09/2018

Printed on 13/09/2018

## **SECTION 15. Information on regulation**

15.1. Legislative and regulatory provisions on health, safety and the environment specific to the substance or mixture

Seveso category - Directive 2012/18/EC: None

Restrictions on the product or substances contained in it according to Annex XVII Regulation (EC) 1907/2006

<u>Product</u>

Point

Substances in Candidate List (Art. 59 REACH)

Based on the available data, the product does not contain SVHC substances in percentages over 0.1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to export notification obligation Reg. (EC) 649/2012:

3

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Health checks

Workers exposed to this chemical agent which is hazardous to the health must undergo health monitoring carried out according to the provisions of art. 41 of Italian Leg. Decree 81 of 9 April 2008 unless the risk for the health and safety of the worker has been deemed irrelevant, according to the provisions of art. 224 paragraph 2.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been produced for the mixture and the substances contained in it.

## **SECTION 16. Other information**

Text of the hazard indications (H) quoted in sections 2-3 of the data sheet:

Met. Corr. 1 Substance or corrosive mixture for metals, category 1

Skin Corr. 1A Skin corrosion, category 1A

Eye Dam. 1 Severe eye damage, category 1

Skin Irrit. 2 Skin irritation, category 2

H290 May be corrosive for metals.

H314 Causes severe skin burns and eye damage.

## COMBICLEAN

Revision no. 8

Revision date 13/09/2018

Printed on 13/09/2018

Page no. 12/12

H318 Causes serious eye damage.

H315 Causes skin irritation.

#### KEY:

- ADR: European agreement for the transport of hazardous goods by road
- CAS NUMBER: Chemical Abstract Service Number
- EC50: Concentration that affects 50% of the population subjected to tests
- EC NUMBER: Identification number in ESIS (European archive of existing substances)
- CLP: Regulation EC 1272/2008
- DNEL: Derived No-Effect Level
- EmS: Emergency Schedule
- GHS: Global harmonised system for the classification and labelling of chemical products
- IATA DGR: Regulation for the transportation of hazardous goods of the international association of air transport
- IC50: Immobilisation concentration of 50% of the population subjected to tests
- IMDG: International maritime code for the transportation of hazardous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identification number of Annex VI of the CLP
- LC50: Lethal concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational exposure limit
- PBT: Persistent, bioaccumulative and toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation EC 1907/2006
- RID: Regulation for international transportation of hazardous goods by train
- TLV: Threshold limit value
- TLV CEILING: Concentration which must not be exceeded at any time during working exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average
- VOC: Volatile organic compound
- vPvB: Very persistent and very bioaccumulative according to REACH
- WGK: Water hazard classes (Germany).

### GENERAL BIBLIOGRAPHY:

- 1. Regulation (EC) 1907/2006 of the European Parliament (REACH)
- 2. Regulation (EC) 1272/2008 of the European Parliament (CLP)
- 3. Regulation (EU) 790/2009 of the European Parliament (I Atp. CLP)
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
- 6. Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
- 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
- 8. Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)
- 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP) 10. Regulation (EU) 2015/1221 of the European Parliament (VII Atp. CLP)
- 11. Regulation (EU) 2016/1221 of the European Parliament (VIII Atp. CLP)
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA Agency website
- Database of SDS models for chemical substances Ministry of Health and Higher Health Institute

## Note for user:

The information contained in this data sheet is based on the knowledge available to us on the data of the latest version. The user must check the suitability and completeness of the information in relation to the specific product use.

This document should not be interpreted as a guarantee of any specific property of the product.

Since the use of the product does not fall directly under our control, the user is obliged to observe the laws and provisions, under his own responsibility, in force concerning safety and hygiene. No responsibility is assumed for improper use.

Provide adequate training for staff in charge of using chemical products.